



BW – BVE













ULTRA-LOW VOLUME ELECTROSTATIC-PNEUMATIC TRAILED SPRAYER WITH CENTRIFUGAL FAN

The BW-BVE is an advanced trailed sprayer designed for ultra-low-volume electrostatic-pneumatic spraying, perfect for table/wine vineyards and orchards. Featuring a newly designed centrifugal fan with double suction and a **lowered polyethylene tank**, it ensures precise treatments with minimal drift and maximum coverage. **Droplets are micronized to 30–60 microns**, with consumption ranging from 70 to 1000 l/ha. The system **reduces fuel consumption** by over 40% and improves treated surfaces by 35–45%, achieving **98% coverage**. The adjustable aeration system delivers air volumes from 10,000 to 80,000 m³/h, suitable for various treatments, including gibberellic products.



Optional: Cleverspray
Electric control 4 sections
\$7000

- Lowered polyethylene tank with circuit and handwashing systems.
- **Hot galvanized steel chassis and conveyor.**
- 180° galvanized steel air diffuser with adjustable deflectors.
- Adjustable overhanging wheel hubs (width and height).
- **ANNOVI REVERBERI brass pump.**
- External filter, self-filling system, and high-pressure agitator.
- Adjustable autosteer drawbar and support wheel.
- **Compliant with CE regulations** and road-approved.
- Anti-drip electrostatic nozzles (70–1000 l/ha).
- Airflow deflector, filter kit for brass arches, and pesticide mixing kit.

MODEL												
BW2000BVE	450 mm	10	1+F	6 - 8 mt	6 - 8 mt	BHS150	150	90/100 hp	2000 LT	L: 390 P: 160 H: 140 cm	902 kg	79,900
BW3000BVE	450 mm	10	1+F	6 - 8 mt	6 - 8 mt	BHS170	170	100/110 hp	3000 LT	L: 415 P: 190 H: 150 cm	950 kg	89,850